

## TECHNICAL DATA

SIZE AND TYPE GROUPING CODE	20' x 8' x 8'6" 20 RE	40' x 8' x 9'6" 40 RH	45'x8'x8'6" 45 RH
DIMENSIONS & TYPE CODE	22 R1	45 R1	LN R1
INTERNAL DIMENSIONS			
Length (mm) l1	5,456	11,584	13,280
Width (mm) w1	2,294	2,294	2,440
Height (mm) h1	2,273	2,557	2,582
DOOR OPENING			
Width (mm) w2	2,290	2,284	2,440
Height (mm) h2	2,264	2,437	2,567
NOMINAL CAPACITY (cu.m)	28.6	58	83,7
MAXIMUM GROSS WEIGHT (kg)	30,480	30,480 / 34,000	34,000
AVERAGE TARE (kg)	3,010	4,140 / 4,700	6,180
MAXIMUM PAYLOAD (kg)	27,470	25,800 / 29,300	27,820
HEIGHT USABLE FOR CARGO (mm)	2,158	2,394	2,482
CAPACITY IN USE (cu.m)	27.3	64.9	80,420
LASHING BARS IN THE VENTILATION FLOOR SIDE GUTTERS			
quantity	4	6	6
resistance (kg/each)	500	1,000	1,000

Some series are certified ATO and/or USDA.  
Fresh air exchange venting system (adjustable).